

Date: Wednesday, 11/21/2007 12:47:36 PM
User: Kim Johnston

Process Sheet

Customer : CU-DAR001 Dart Helicopters Services	Drawing Name : SADDLE FITTING, FWD (OUTBOARD/INBOARD)
Job Number : 35915	
Estimate Number : 10530	
P.O. Number : <i>N/A</i>	Part Number : D2571
This Issue : 11/21/2007 S.O. No. : <i>N/A</i>	Drawing Number : D2571 REV E
Prsht Rev. : NC	Project Number : N/A
First Issue : <i>N/A</i>	Drawing Revision : E
Previous Run : 34812	Material : <i>N/A</i>
Written By : <i>[Signature]</i>	Due Date : 1/15/2008
Checked & Approved By : <i>[Signature]</i>	Qty: 12 Um: Each
Comment : Est. 102.10.02 Re-format; Change to Dwg Rev. D & incorporated D2572 KJ	

Additional Product

Job Number:



Seq. #: Machine Or Operation: Description :

1.0 D6101007 7075-T7351 8.25X7.75X2.5



Comment: Qty.: 1.0000 Each(s)/Unit Total : 12.0000 Each(s)
7075-T7351 8.25X7.75X2.5
Make from D6101-007 billet for D2571
Ensure that grain is along 7.75" length
Batch No: *B31389*

ML 07/12/27

(12)

2.0 HAAS1 -HAAS CNC VERTICAL MACHINING #1



Comment: HAAS CNC VERTICAL MACHINING #1
Program Batch No. *35915* Double check by: *DSP*

- 1-Machine Step No 1 per Folio FA051 and inspect per attached Dimension Sheets
- 2-Machine Step No 2 per Folio FA051 and inspect per attached Dimension Sheets
- 3-Machine Step No 3 per Folio FA051 and inspect per attached Dimension Sheets
- 4-Deburr and remove all machining marks
- 5-Tumble to remove sharp edges.

ML SF 08/01/03

(12)

3.0 MILLING CONV. CONVENTIONAL MILLING MACHINE



Comment: CONVENTIONAL MILLING MACHINE
Machine keyway as per dwg D2571 & D2572

ML SF 08/01/03

(12)

4.0 QC2 INSPECT PARTS AS THEY COME OFF MACHINE



Comment: INSPECT PARTS AS THEY COME OFF MACHINE

ML SF 08/01/03

(12)

W/O:		WORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector

Part No: _____ PAR #: _____ Fault Category: _____ NCR: Yes ☒ No ☐ DQA: D Date: 28/01/11
 QA: N/C Closed: _____ Date: _____

NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			

NOTE: Date & initial all entries

Date: Wednesday, 11/21/2007 12:47:36 PM
User: Kim Johnston

Process Sheet

Customer: CU-DAR001 Dart Helicopters Services

Drawing Name: SADDLE FITTING, FWD (OUTBOARD/INBOARD)

Job Number: 35915

Part Number: D2571

Job Number:



Seq. #:

Machine Or Operation:

Description :

5.0

QC8

SECOND CHECK



Comment: SECOND CHECK

SD 08/01/04

(12)

6.0

HAND FINISHING1

HAND FINISHING RESOURCE #1



Comment: HAND FINISHING RESOURCE #1

Acid etch and Alodine as per QSI 005 4.1

m-h

08/01/08

(12x)

7.0

POWDER COATING

POWDER COATING



Comment: POWDER COATING

* Powder **SANDTEX GREEN**
(Ref: 4.3.5.1) as per QSI 005 4.3

M102316

m-h

08/01/09

(12x)

8.0

QC3

INSPECT POWDER COAT/CHEMICAL CONVERSION



Comment: INSPECT POWDER COAT

jd

08-01-09

12

9.0

PACKAGING 1

PACKAGING RESOURCE #1



Comment: PACKAGING RESOURCE #1

Identify and Stock

Location: _____

8/1/9 SD

(12x)

10.0

QC21

FINAL INSPECTION/W/O RELEASE



Comment: FINAL INSPECTION/W/O RELEASE

2008/01/11

Job Completion



U 28-00-11

W/O:		WORK ORDER CHANGES					
DATE	STEP	PROCEDURE CHANGE	By	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector

Part No: _____ PAR #: _____ Fault Category: _____ NCR: Yes No DQA: _____ Date: _____

QA: N/C Closed: _____ Date: _____

NCR:		WORK ORDER NON-CONFORMANCE (NCR)						
DATE	STEP	Description of NC Section A	Corrective Action Section B			Verification Section C	Approval Chief Eng	Approval QC Inspector
			Initial Chief Eng	Action Description Chief Eng	Sign & Date			

NOTE: Date & initial all entries

DART AEROSPACE LTD	Work Order:	35915
Description: Saddle, Fwd Outboard	Part Number:	D2571
Inspection Dwg: D2571 Rev. E		Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2571 Rev. E and record below:

				Recorded Actual Dimensions					
Dim	Min	Max	Go/No Go Gauge	1	2	3	4	By	Date
A	0.438	0.443	DT8682	0.440	.440	.440	.440		
B	1.745	1.755		1.750	1.750	1.750	1.750		
C	3.495	3.505		3.500	3.500	3.500	3.500		
D	1.745	1.755		1.750	1.750	1.750	1.750		
E	7.990	8.010		7.998	7.999	8.000	8.000		
F	0.490	0.510		0.501	.500	.500	.500		
G	0.257	0.262	DT8683	0.260	.258	.259	.259		
H	0.375	0.380	DT8684	0.377	.377	.377	.377		
I	0.490	0.510		0.499	.500	.500	.500		
J	1.174	1.184		1.178	1.180	1.180	1.180		
K	0.558	0.578		0.567	.568	.577	.570		
L	1.174	1.184		1.178	1.180	1.180	1.180		
M	1.490	1.500		1.494	1.500	1.500	1.500		
N	2.495	2.505		2.499	2.500	2.500	2.500		
O	3.869	3.879		3.872	3.872	3.872	3.872		
P	0.115	0.135		0.126	.126	.127	.127		
Q	0.115	0.135		0.135	.130	.130	.130		
R	0.240	0.260		0.249	.246	.251	.251		
S	0.115	0.135		0.129	.129	.129	.129		
T	0.178	0.198		0.188	0.188	0.188	0.188		
U	2.940	2.980		2.960	2.960	2.960	2.960		
V	0.230	0.250		0.236	.240	.241	.240		
W	0.115	0.135		0.120	.134	.131	.130		
X	0.308	0.313		0.310	.311	.311	.311		
Y	0.760	0.765		0.760	.760	.760	.760		
Z	0.352	0.372		0.365	.365	.365	.365		
AA	0.470	0.530		0.500	0.500	0.500	0.500		
AB	0.615	0.635		0.632	.632	.632	.632		
AC	0.053	0.073		0.063	0.063	0.063	0.063		
AD	0.240	0.260		0.246	.250	.250	.250		
AE	1.375	1.395		1.388	1.386	1.386	1.386		
AF	0.115	0.135		0.127	.127	.127	.127		
AG	0.240	0.280		0.250	.250	.260	.260		
AH	0.240	0.260		0.247	.247	.250	.250		
AI	2.000	2.020		2.002	2.001	2.000	2.000		
AJ	0.023	0.043		0.033	.033	.033	.033		
Accept/Reject									

Measured by:	MR / SF
Date:	03/12/25

Audited by:	SA
Date:	08/01/04

Rev	Date	Change	Revised by	Approved
A		New Issue	RF	
B	02.09.24	Re-format; Added Rev. D	KJ	
C	02.10.11	Re-format; Added DT8682, DT8683, DT8684	KJ	
D	05.05.05	Added dimension AI	KJ/RF	
E	05.12.05	Added dimension AJ	KJ/JLM	

DART AEROSPACE LTD		Work Order:	35915
Description: Saddle, Fwd Outboard		Part Number:	D2571
Inspection Dwg: D2571 Rev. E		Page 1 of 1	

Inspect dimensions highlighted on inspection sheet drawing D2571 Rev. E and record below:

				Recorded Actual Dimensions					
Dim	Min	Max	Go/No Go Gauge	SA	62	73	44	By	Date
A	0.438	0.443	DT8682	.440	.440	.440	.441		
B	1.745	1.755		1.750	1.750	1.750	1.750		
C	3.495	3.505		3.500	3.500	3.500	3.500		
D	1.745	1.755		1.750	1.750	1.750	1.750		
E	7.990	8.010		8.000	8.000	8.000	8.000		
F	0.490	0.510		.500	.500	.503	.504		
G	0.257	0.262	DT8683	.260	.260	.260	.260		
H	0.375	0.380	DT8684	.376	.377	.377	.377		
I	0.490	0.510		.500	.500	.500	.500		
J	1.174	1.184		1.180	1.180	1.180	1.180		
K	0.558	0.578		.568	.568	.568	.568		
L	1.174	1.184		1.180	1.180	1.180	1.180		
M	1.490	1.500		1.500	1.500	1.500	1.500		
N	2.495	2.505		2.500	2.500	2.500	2.500		
O	3.869	3.879		3.874	3.874	3.874	3.874		
P	0.115	0.135		.125	.125	.125	.125		
Q	0.115	0.135		.125	.125	.125	.135		
R	0.240	0.260		.250	.250	.250	.248		
S	0.115	0.135		.125	.125	.125	.132		
T	0.178	0.198		.188	.188	.188	.188		
U	2.940	2.980		2.963	2.963	2.963	2.963		
V	0.230	0.250		.240	.240	.240	.238		
W	0.115	0.135		.125	.125	.125	.133		
X	0.308	0.313		.311	.310	.310	.310		
Y	0.760	0.765		.760	.760	.760	.760		
Z	0.352	0.372		.360	.364	.364	.364		
AA	0.470	0.530		.500	.500	.500	.500		
AB	0.615	0.635		.629	.629	.629	.623		
AC	0.053	0.073		.063	.063	.063	.063		
AD	0.240	0.260		.250	.250	.250	.247		
AE	1.375	1.395		1.385	1.385	1.385	1.388		
AF	0.115	0.135		.125	.125	.125	.130		
AG	0.240	0.280		.260	.260	.260	.260		
AH	0.240	0.260		.260	.250	.250	.248		
AI	2.000	2.020		2.000	2.000	2.000	2.000		
AJ	0.023	0.043		.033	.033	.033	.033		
Accept/Reject									

Measured by: JS
Date: 07/12/04 / 08/01/02

Audited by: SA
Date: 08/01/04

Rev	Date	Change	Revised by	Approved
A		New Issue	RF	
B	02.09.24	Re-format; Added Rev. D	KJ	
C	02.10.11	Re-format; Added DT8682, DT8683, DT8684	KJ	
D	05.05.05	Added dimension AI	KJ/RF	
E	05.12.05	Added dimension AJ	KJ/JLM	

DART AEROSPACE LTD	Work Order:	3915
Description: Saddle, Fwd Outboard	Part Number:	D2571
Inspection Dwg: D2571 Rev. E		Page 1 of 1

Inspect dimensions highlighted on inspection sheet drawing D2571 Rev. E and record below:

				Recorded Actual Dimensions					
Dim	Min	Max	Go/No Go Gauge	9A	10	11	12	By	Date
A	0.438	0.443	DT8682	.440	.440	.440	.440		
B	1.745	1.755		1.750	1.750	1.750	1.750		
C	3.495	3.505		3.500	3.500	3.500	3.500		
D	1.745	1.755		1.750	1.750	1.750	1.750		
E	7.990	8.010		8.000	8.000	8.007	8.001		
F	0.490	0.510		.500	.500	.501	.501		
G	0.257	0.262	DT8683	.258	.260	.260	.260		
H	0.375	0.380	DT8684	.377	.376	.377	.377		
I	0.490	0.510		0.500	.501	.501	.501		
J	1.174	1.184		1.180	1.179	1.179	1.180		
K	0.558	0.578		0.568	.569	.568	.568		
L	1.174	1.184		1.160	1.179	1.179	1.180		
M	1.490	1.500		1.500	1.494	1.499	1.500		
N	2.495	2.505		2.500	2.499	2.500	2.500		
O	3.869	3.879		3.874	3.873	3.873	3.873		
P	0.115	0.135		.125	.124	.125	.125		
Q	0.115	0.135		0.135	.135	.135	.135		
R	0.240	0.260		.250	.248	.250	.250		
S	0.115	0.135		0.132	.132	.132	.132		
T	0.178	0.198		.188	.188	.188	.188		
U	2.940	2.980		2.963	2.960	2.963	2.963		
V	0.230	0.250		0.238	.241	.240	.241		
W	0.115	0.135		0.132	.132	.130	.130		
X	0.308	0.313		.310	.310	.310	.310		
Y	0.760	0.765		.760	.760	.760	.760		
Z	0.352	0.372		.360	.360	.360	.360		
AA	0.470	0.530		.500	.500	.500	.500		
AB	0.615	0.635		.630	.630	.630	.630		
AC	0.053	0.073		.063	.063	.063	.063		
AD	0.240	0.260		.250	.247	.245	.245		
AE	1.375	1.395		1.388	1.386	1.386	1.386		
AF	0.115	0.135		0.130	.130	.130	.130		
AG	0.240	0.280		.260	.260	.260	.260		
AH	0.240	0.260		0.247	.248	.255	.260		
AI	2.000	2.020		2.000	2.000	2.000	2.000		
AJ	0.023	0.043		.033	.033	.033	.033		
Accept/Reject									






Measured by: S.F.
Date: 02/12/31 / 08/02/01






Audited by: J.A.
Date: 08/01/04

Rev	Date	Change	Revised by	Approved
A		New Issue	RF	
B	02.09.24	Re-format; Added Rev. D	KJ	
C	02.10.11	Re-format; Added DT8682, DT8683, DT8684	KJ	
D	05.05.05	Added dimension AI	KJ/RF	
E	05.12.05	Added dimension AJ	KJ/JLM	

05.12.06




MATERIAL: 7075-T7351 (QQ-A-250/12) (REF DART SPEC. D6102-001)
FINISH: ACID ETCH, ALODINE PER DART QSI 005 4.1
POWDER COAT GLOSS WHITE (REF 4.3.5.1) PER DART
QSI 005 4.3
BREAK ALL SHARP EDGES 0.010 TO 0.020
TOLERANCES ARE PER DART QSI 018 UNLESS OTHERWISE NOTED

- | | |
|---|--|
|  | ENGRAVE PART AND BATCH NUMBER IN THIS AREA TO MAX DEPTH OF 0.010 |
|  | ENGRAVE DART LOGO TO MAX DEPTH OF 0.015 WITH MIN RAD 0.125 |
|  | CHAMFER 0.063" x 45° AROUND THIS SURFACE (TYPICAL 2 PLACES) |
|  | CHAMFER 0.063" x 45° ALL AROUND |
|  | CHAMFER 0.033" x 45° (SEE DETAIL C) |



SECTION A-A

DETAIL C
SCALE 4:3

E	05.07.13	ADD CHAMFER ON RIDGE, NOTE 5
D	02.09.06	ADD RIDGES; TIGHTEN TOLERANCES
C	99.10.22	INCORP. DEO 9123/9079/9102 ADD DIMENSIONS PER TSR A1177
B	96.12.02	ADD GRAIN DIR., 0.438 WAS 0.425
A	96.09.16	NEW ISSUE
DESIGN DS	DRAWN BY PH	 DART AEROSPACE LTD. HAWKSBURY, ONTARIO, CANADA
CHECKED 	APPROVED 	DRAWING NO. D2571
DATE 05.07.13	TITLE OUTER FWD SADDLE	

5) SHOP COPY
RETURN TO
ENGINEERING
UNCONTROLLED COPY
SUBJECT TO AMENDMENT
WITHOUT NOTICE
WORK ORDER
NO. 35915